

Serial No. 10/660,952

RECEIVED
CENTRAL FAX CENTER

APR 09 2007

IN THE CLAIMS

Please cancel claims 3, 12 and 21, and amend claims 1, 4, 5, 10, 13, 14, 19, 22 and 23 as follows:

1. (CURRENTLY AMENDED) A method of automatic measurement of audio presence and level by direct processing of a data stream representing an audio signal, comprising:
 - (a) extracting sub-band data from the data stream;
 - (b) dequantizing and denormalizing the extracted sub-band data;
 - (c) measuring an audio level for the dequantized and denormalized sub-band data without reconstructing the audio signal using channel characteristics; and
 - (d) comparing the measured audio level against at least one threshold.
2. (ORIGINAL) The method of claim 1, further comprising using a psychoacoustic model in determining a perceived level of the measured audio signal according to human ear sensitivity.
3. (CANCELED)
4. (CURRENTLY AMENDED) The method of claim [[3]] 1, wherein the channel characteristics are used to weight an instantaneous level.
5. (CURRENTLY AMENDED) The method of claim [[3]] 1, wherein the channel characteristics are used to weight an overall level.
6. (ORIGINAL) The method of claim 1, wherein the sub-band data represents the audio signal's power in each frequency band represented by each sub-band at a particular point in time.
7. (ORIGINAL) The method of claim 1, further comprising averaging the audio level over time.
8. (ORIGINAL) The method of claim 1, further comprising thresholding the audio level.

Serial No. 10/660,952

9. (ORIGINAL) The method of claim 1, further comprising triggering an alarm when the threshold is exceeded.

10. (CURRENTLY AMENDED) An apparatus for automatic measurement of audio presence and level by direct processing of a data stream representing an audio signal, comprising:

- (a) means for extracting sub-band data from the data stream;
- (b) means for dequantizing and denormalizing the extracted sub-band data;
- (c) means for measuring an audio level for the dequantized and denormalized sub-band data without reconstructing the audio signal using channel characteristics; and
- (d) means for comparing the measured audio level against at least one threshold.

11. (ORIGINAL) The apparatus of claim 10, further comprising means for using a psychoacoustic model in determining a perceived level of the measured audio signal according to human ear sensitivity.

12. (CANCELED)

13. (CURRENTLY AMENDED) The apparatus of claim ~~[[12]]~~ 10, wherein the channel characteristics are used to weight an instantaneous level.

14. (CURRENTLY AMENDED) The apparatus of claim ~~[[12]]~~ 10, wherein the channel characteristics are used to weight an overall level.

15. (ORIGINAL) The apparatus of claim 10, wherein the sub-band data represents the audio signal's power in each frequency band represented by each sub-band at a particular point in time.

16. (ORIGINAL) The apparatus of claim 10, further comprising means for averaging the audio level over time.

17. (ORIGINAL) The apparatus of claim 10, further comprising means for thresholding the audio level.

Serial No. 10/660,952

18. (ORIGINAL) The apparatus of claim 10, further comprising means for triggering an alarm when the threshold is exceeded.

19. (CURRENTLY AMENDED) An article of manufacture comprising a program storage device embodying logic for instructions that, when executed by a processor, result in the processor performing a method of automatic measurement of audio presence and level by direct processing of a data stream representing an audio signal, comprising:

- (a) extracting sub-band data from the data stream;
- (b) dequantizing and denormalizing the extracted sub-band data;
- (c) measuring an audio level for the dequantized and denormalized sub-band data without reconstructing the audio signal using channel characteristics; and
- (d) comparing the measured audio level against at least one threshold.

20. (ORIGINAL) The article of claim 19, further comprising using a psychoacoustic model in determining a perceived level of the measured audio signal according to human ear sensitivity.

21. (CANCELED)

22. (CURRENTLY AMENDED) The article of claim [[21]] 19, wherein the channel characteristics are used to weight an instantaneous level.

23. (CURRENTLY AMENDED) The article of claim [[21]] 19, wherein the channel characteristics are used to weight an overall level.

24. (ORIGINAL) The article of claim 19, wherein the sub-band data represents the audio signal's power in each frequency band represented by each sub-band at a particular point in time.

25. (ORIGINAL) The article of claim 19, further comprising averaging the audio level over time.

26. (ORIGINAL) The article of claim 19, further comprising thresholding the audio level.

Serial No. 10/660,952

27. (ORIGINAL) The article of claim 19, further comprising triggering an alarm when the threshold is exceeded.